

Kelin ၀၀၀၀ ၀၀ ၀၀၀ ၀၀၀၀ ၀၀၀၀ ၀၀ ၀၀၀ ၀၀ ၀၀၀၀ ၀၀ ၀၀၀ ၀၀၀၀၀ ၀ ၀၀၀၀, ၀၀၀၀ ၀၀ ၀၀၀ ၀၀ ၀၀၀၀ ၀ Kelin ၀၀၀၀ ၀ ၀၀၀၀ ၀၀၀ ၀၀၀ ၀၀၀ ၀၀၀၀၀ ၀၀၀ ၀၀၀၀၀ ၀၀ ၀၀၀၀ ၀၀ ၀၀၀၀ ၀၀၀၀. ၀၀၀၀ ၀၀, ၀၀၀ ၀၀ ၀ ၀၀၀ ၀၀ ၀၀ ၀၀ ၀၀၀၀၀. ၀၀၀ ၀၀၀၀ ၀၀ ၀၀၀ ၀၀၀၀၀. ၀၀၀ ၀၀၀ ၀၀ ၀၀၀၀၀ ၀၀၀ ၀၀၀ ၀၀, ၀၀၀၀, ၀၀၀ ၀၀ ၀ ၀၀၀၀ ၀၀၀၀၀၀. ၀၀၀ ၀ ၀၀ ၀ ၀၀ ၀၀၀ ၀၀၀ ၀၀ ၀၀၀၀၀ ၀၀၀၀ ၀၀၀ ၀၀ ၀၀၀၀ ၀၀၀၀. ၀၀ ၀၀၀၀ ၀၀၀၀ ၀၀ ၀ ၀၀၀၀၀ ၀၀၀၀. ၀၀ ၀၀၀ ၀၀၀ ၀၀၀ ၀ ၀၀၀၀ ၀၀၀ ၀၀၀ ၀၀၀၀ ၀၀၀၀. ၀ ၀၀၀ ၀၀၀ ၀၀, ၀၀, ၀၀, ၀၀၀ ၀၀၀၀ ၀၀ ၀၀ ၀၀, ၀၀, ၀၀ ၀၀ ၀၀၀၀ ၀၀၀ ၀ ၀ ၀၀၀ ၀ ၀၀၀ ၀. ၀၀ ၀၀ ၀၀ ၀၀ ၀၀၀ ၀ ၀၀ ၀၀၀ ၀၀၀ ၀၀ ၀၀၀၀ ၀၀၀ ၀၀ ၀၀ ၀၀၀ ၀၀ ၀၀ ၀၀၀ ၀၀၀၀ ၀၀၀၀.



၀၀၀ ၀၀၀ ၀၀၀ ၀၀. ၀၀ ၀၀၀ ၀၀ ၀၀၀ ၀၀၀၀၀၀.

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack







01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□□□ □□□ □□□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Perching Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



□□ □□ □□



□□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□

□□

