

Kelin Epoxy 係 一種 無毒 無味 無臭 之 環氧樹脂 塗料。 具有 優良 之 附著力 及 耐磨性。 且 能 防止 水、油、酸、鹼 之 滲透 及 腐蝕。 適合 用於 各種 建築 工程 之 防銹、防腐、防污、防塵 等 用途。 其 優點 如下：

1. 堅固耐用：經久耐用，不易磨損。  
2. 防腐防銹：能防止金屬表面之氧化及腐蝕。  
3. 防污防塵：易於清潔，保持環境衛生。  
4. 美觀大方：顏色多樣，可與環境相協調。  
5. 施工簡便：可刷塗、噴塗或滾塗。  
6. 無毒無味：不含揮發性有機物，施工後無異味。



歡迎 垂詢 洽談。 電話 0900 000000。

-  Gray 1#
-  Gray 2#
-  Gray 3#
-  Gray 4#
-  Gray 5#
-  Gray 6#
-  Gray 7#
-  Gray 8#
-  Gray 9#
-  Cement Gray
-  Dull Gray
-  Silver Gray
-  Metal Gray
-  Luxury Silver
-  Glacier White
-  Calaeatta
-  Pearl Gold
-  Slate Gray
-  Terra Brown
-  Greyish Green
-  Yellow Gray
-  Soft Khaki
-  Yellowish Brown
-  Olive Brown
-  Brownness
-  Dark Brown
-  Reddish Brown
-  Rock Bslack



□ □ □ □ □ □ □ □ □ □






01

Clean the tiles and keep it dry



02

Polish with tile wax except the glazed tile



03

Open & Watch, both sides can extruded meanwhile



04

Screw on the nozzle, put on the grout gun




05

Inclined cut the top of the nozzle in 45°



06

Squeeze out 60-80cm long grout in the forepart



07

Evenly squeeze out the tile agent along the gap




08

Press the grout with professional glue-press tools



09

Don't touch in 4-5 hours and remove excess grout then.



10

Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02



03



04



05



06



07



08



09

Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

