

Kelin Epoxy 係 一種 雙組份 環氧樹脂 填縫劑，具有 極強 之 粘合力 及 耐用性。適用於 各種 不同 之 填縫 工程。無論 室內 或 室外，均 可 使用。其 優點 包括：易於 施工、乾燥 快、無 塵、無 臭、且 能 抵抗 酸鹼 之 腐蝕。此外，其 表面 可 磨光 至 鏡面 效果，使 填縫 處 與 瓷磚 完美 融合。Kelin Epoxy 係 填縫 工程 之 最佳 選擇。請 向 我們 查詢 詳情。



請 向 我們 查詢 詳情。電話：000 000 00。

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



□□ □ □ □□□ □□□□□





01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Perching Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



□□ □□



□□□ □□



□□ □□ □□



□□ □□



□□ □□ □□



□□ □□



□□ □□ □□



□□ □□

□□

