





**Polyurea** □ □ □ □ □ □

ENVIRONMENTAL ( construction solid about 80-100%)

CONVENIENT CONSTRUCTION  
(traditional construction method)

WATER PROOF (0.6mm Polyurea=2mm Polyurethane)

**3<sup>rd</sup> GENERATION  
POLYUREA BASIC**

WEATHER RESISTANCE (qvb2000h)

ENERGY CONSERVATION  
( -5°Csolidify , primary film formation is 375um)

WEAR RESISTANCE (750g/500 times abrasion loss 30mg)  
CORROSION RESISTANCE (salt fog resistance for 2000h)

□ □ □ □ □ □






01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile




04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart




07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 2-4 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Perching Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□





□□ □□



□□

