

සමස්ත ඉංජිනේරු කටයුතු සඳහා සුදුසු වන පරිදි නිවැරදි තේරුම් ගැනීම සඳහා වැදගත් වේ. තේරුම් ගැනීම, වැඩ කිරීම, ආලේප කිරීම සඳහා වන පරිදි, වැඩ කිරීමේ ක්ෂේත්‍රය වලදී ඉහත සඳහන් කර ඇති තේරුම් ගැනීමේ ක්‍රමවේදයන් භාවිත කර ගැනීම සඳහා වේ. මෙහිදී වැඩ කිරීමේ ක්ෂේත්‍රය වලදී ඉහත සඳහන් කර ඇති තේරුම් ගැනීමේ ක්‍රමවේදයන් භාවිත කර ගැනීම සඳහා වේ. මෙහිදී වැඩ කිරීමේ ක්ෂේත්‍රය වලදී ඉහත සඳහන් කර ඇති තේරුම් ගැනීමේ ක්‍රමවේදයන් භාවිත කර ගැනීම සඳහා වේ. මෙහිදී වැඩ කිරීමේ ක්ෂේත්‍රය වලදී ඉහත සඳහන් කර ඇති තේරුම් ගැනීමේ ක්‍රමවේදයන් භාවිත කර ගැනීම සඳහා වේ.



සමස්ත ඉංජිනේරු කටයුතු සඳහා සුදුසු වන පරිදි නිවැරදි තේරුම් ගැනීම සඳහා වැදගත් වේ.



□□ □□ □ □□□ □□






01
Clean the tiles and keep it dry



02
Polish with tile wax except the glazed tile



03
Open & Watch, both sides can extruded meanwhile




04
Screw on the nozzle, put on the grout gun



05
Inclined cut the top of the nozzle in 45°



06
Squeeze out 60-80cm long grout in the forepart




07
Evenly squeeze out the tile agent along the gap



08
Press the grout with professional glue-press tools



09
Don't touch in 4-5 hours and remove excess grout then.



10
Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02
Cutter Knife



03
Pointing trowel



04
Brush



05
Forming Stick



06
Perching Knife



07
Masking Tape



08
Stainless Steel Ball



09
Cleaning Awl

□□ □□



□□ □□



□□ □□ □□



□□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□

□□

