

Kelin Epoxy 係 一種 高品質 之 建築 材料， 具有 極佳 之 粘結 力 及 耐用 性。 此 材料 可 應用 於 各種 建築 工程， 如 牆面 修補、 地板 修補、 浴室 修補 等。 此外， 此 材料 亦 具有 防霉、 防水 之 優點。 因此， 建築 師 及 裝修 工人 均 喜 採用 此 材料。 此 材料 之 優點 如下：

1. 粘結 力 強： 此 材料 能 牢固 粘結 各種 建築 材料， 如 磚塊、 瓷磚、 石膏 等。

2. 耐用 性 高： 此 材料 能 抵抗 各種 環境 因素 之 侵蝕， 如 潮濕、 酸鹼 等。

3. 防霉 防水： 此 材料 能 有效 防止 霉菌 之 滋生 及 水分 之 滲透。

4. 易於 施工： 此 材料 之 施工 簡便， 且 乾燥 時間 短。

5. 顏色 多樣： 此 材料 有 各種 顏色 可供 選擇， 以 配合 建築 工程 之 設計。



此 材料 之 優點 如下：








01

Clean the tiles and keep it dry



02

Polish with tile wax except the glazed tile



03

Open & Watch, both sides can extruded meanwhile



04

Screw on the nozzle, put on the grout gun




05

Inclined cut the top of the nozzle in 45°



06

Squeeze out 60-80cm long grout in the forepart



07

Evenly squeeze out the tile agent along the gap



08

Press the grout with professional glue-press tools



09

Don't touch in 4-5 hours and remove excess grout then.



10

Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02



03



04



05



06



07



08



09

Cutter Knife

Pointing trowel

Brush

Forming Stick

Pointing Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

