

Kelin Polyurea 係 一種 耐用 且 易 於 安裝 之 塗料。 此 塗料 具有 防腐、 耐磨、 耐水、 耐油 等 優點， 且 能 與 各種 基面 良好 結合， 形 成 一 層 致密 之 保護 膜。 此 塗料 可 用於 各種 工業 及 民 用 建築 之 防 腐 及 修 補。 其 優點 包括 施工 簡便、 乾 燥 快 速、 無 毒 無 害、 且 能 保 持 長 久 之 耐用 性。 此 塗料 係 一 種 真正 之 " 永 久 保 護 膜 "。

此 塗料 係 由 德 國 著 名 之 科 林 有 限 公 司 研 究 開 發 出 來 之 產 品。 該 公 司 具 有 14 年 之 研 究 及 開 發 經 驗， 且 具 有 充 足 之 R & D 實 力。 此 塗料 係 一 種 真正 之 永 久 保 護 膜。 其 優點 包括 施工 簡便、 乾 燥 快 速、 無 毒 無 害、 且 能 保 持 長 久 之 耐用 性。



此 塗料 係 一 種 真正 之 永 久 保 護 膜。

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



□ □ □ □ □ □ □ □ □ □





01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Pointing Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

