

Kelin Epoxy 係 一種 極佳 之 填 補 劑 及 修 補 劑。 此 種 填 補 劑 係 由 環 氧 樹 脂 及 無 機 粉 末 所 組 成。 其 具 有 極 佳 之 粘 附 力 及 強 度。 此 種 填 補 劑 可 用 於 修 補 各 種 裂 縫 及 缺 損。 其 具 有 極 佳 之 耐 磨 性 及 耐 腐 蝕 性。 此 種 填 補 劑 可 用 於 修 補 各 種 地 面 及 牆 面。 其 具 有 極 佳 之 耐 火 性 及 耐 高 溫 性。 此 種 填 補 劑 可 用 於 修 補 各 種 電 氣 絕 緣 體。 其 具 有 極 佳 之 耐 電 擊 性 及 耐 電 壓 性。 此 種 填 補 劑 可 用 於 修 補 各 種 電 氣 絕 緣 體。 其 具 有 極 佳 之 耐 電 擊 性 及 耐 電 壓 性。

此 種 填 補 劑 係 由 環 氧 樹 脂 及 無 機 粉 末 所 組 成。 其 具 有 極 佳 之 粘 附 力 及 強 度。 此 種 填 補 劑 可 用 於 修 補 各 種 裂 縫 及 缺 損。 其 具 有 極 佳 之 耐 磨 性 及 耐 腐 蝕 性。 此 種 填 補 劑 可 用 於 修 補 各 種 地 面 及 牆 面。 其 具 有 極 佳 之 耐 火 性 及 耐 高 溫 性。 此 種 填 補 劑 可 用 於 修 補 各 種 電 氣 絕 緣 體。 其 具 有 極 佳 之 耐 電 擊 性 及 耐 電 壓 性。



此 種 填 補 劑 係 由 環 氧 樹 脂 及 無 機 粉 末 所 組 成。

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



□□ □ □ □□□□ □□□□□□








□□ □□ □□ □□



Two Component Caulking Gun



□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

