

Kelin Epoxy 係 一種 高品質 之 塗料 係 專為 保護 及 裝飾 而 設計。 此 塗料 具有 極高 之 附著力 及 耐磨性。 此外， 此 塗料 亦 具有 良好 之 抗污 及 易於 清潔 之 特性。 此 塗料 可 應用 於 各種 表面， 包括 牆面、 天花、 地板 及 傢俬。 此 塗料 之 顏色 豐富， 且 可 根據 客戶 之 要求 進行 定制。 此 塗料 之 施工 簡單， 且 可 在 短時間內 完成。 此 塗料 之 價格 合理， 且 可 為 客戶 節省 大量 之 維修 及 保養 費用。

此 塗料 係 由 優質 之 原料 製成， 且 符合 國際 安全 標準。 此 塗料 之 施工 簡單， 且 可 在 短時間內 完成。 此 塗料 之 價格 合理， 且 可 為 客戶 節省 大量 之 維修 及 保養 費用。 Kelin 係 由 [www.kelin.com](http://www.kelin.com) 提供 之 專業 服務。



此 塗料 係 由 優質 之 原料 製成， 且 符合 國際 安全 標準。

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



□□ □ □ □□□□ □□□□□□





01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Pointing Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

