

Kelin Epoxy 係 一種 高品質 之 環氧 樹脂 膠水 產品。 此 膠水 係 由 兩 種 液體 組 成， 經 過 攪 拌 後 可 變 成 固 體。 此 膠水 具 有 極 高 之 粘 附 力， 且 能 與 多 種 材 質 緊 密 結 合。 此 膠水 亦 具 有 極 高 之 耐 磨 損 力， 且 能 保 持 長 久 之 光 澤。 此 膠水 之 應 用 範 疇 極 廣， 包 括 地 面 鋪 設、 牆 面 鋪 設、 廚 房 鋪 設、 衛 浴 鋪 設 等。 此 膠水 之 價 值 實 屬 廉 宜， 且 易 於 施 工。 此 膠水 係 一 種 極 佳 之 選 擇。



此 膠水 係 一 種 極 佳 之 選 擇。 此 膠水 係 一 種 極 佳 之 選 擇。







Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun



Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forepart




Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.



Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□ □□



□□ □□



□□ □□ □□



□□□ □□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□ □□ □□



□□ □□ □□



□□ □□ □□

□□

