

Kelin 0000 00 0000 00000 00000 00 0000 00 00000 00 00000 00000 00000 00000 00
0 00 00000 0000 0000 0000 0 00 00000 000000. 00000 00, 0000 00 0 0000 00 0000000. 0000 00000 00 00
0 0000000. 0000 0000 00 0000000 0000 0000 00, 00000, 0000 00 0 00000 0000000000. 00000 00 0 00 0000 0000 00 0000000 0
0000 0000 00 000000 00000. 00 00000 00000 00 0 0000000 000000. 00 0000 0000 0000 0000000 0000 0000 0000000000. 0 0
00 0000 00, 00, 00, 0000 00000 00 00 00, 00, 00 00 00000 0000 0 0 0000 0 00000. 0000 [00_00_00_00_0000_0_00_0_0](#)
0. 00 00 00 00 0000 0 00 0000 0000 00 00000 0000 00 00 0000 00 00 0000 0000000 00000.



000 0000 0000 00. 00 0000 00 0000 00000000.

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack







01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□□□ □□□ □□□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Perching Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



□□ □□ □□



□□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□

□□

