

Kelin 2000 2000 2000 2000 2000 2000. 2000, 2000, 2000 2000 2000 2000, 2000, 2000, 2000 2000 2000 2000 2000. 2000 2000, 2000 2000 2000 2000 2000 2000. 2000 2000 2000, 2000, 2000 2000, 2000 2000 2000 2000 2000 2000. 2000 2000 2000 2000 2000 2000 2000 2000 2000 2000 2000 2000. 2000 2000 2000 2000 2000 2000 2000 2000 2000 2000. 2000 2000 2000 2000 2000 2000 2000 2000 2000 2000. Kelin 2000 2000 2000 2000 2000 2000.



2000 2000 2000 2000. 2000 2000 2000 2000.



□□ □□ □ □□□ □□






01

Clean the tiles and keep it dry




02

Polish with tile wax except the glazed tile



03

Open & Watch, both sides can extruded meanwhile



04

Screw on the nozzle, put on the grout gun



05

Inclined cut the top of the nozzle in 45°



06

Squeeze out 60-80cm long grout in the forefront



07

Evenly squeeze out the tile agent along the gap



08

Press the grout with professional glue-press tools



09

Don't touch in 4-5 hours and remove excess grout then.



10

Keep the tiles dry in 24 hours

□□□□ □□□ □□□ □□



Two Component Caulking Gun



02



03



04



05



06



07



08



09

Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□ □□



□□ □□



□□ □□ □□



□□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□

□□

