

Kelin Epoxy သည် ပျော်ကန်စွာ အသုံးပြုနိုင်ပြီး အသုံးပြုရာတွင် ပြုပြင်ဆင်နွေးမှု မလိုအပ်ပါ။

ကျွန်ုပ်တို့သည် **M. manufacturer** ၏ မြန်မာနိုင်ငံရှိ အဓိကထုတ်ကုန်စက်ရုံဖြစ်ပြီး မြန်မာနိုင်ငံတစ်ဝှမ်းသို့ အသုံးပြုသူများအား ရောင်းချနေဆဲဖြစ်ပါသည်။



ကျွန်ုပ်တို့၏ မြန်မာနိုင်ငံရှိ အဓိကထုတ်ကုန်စက်ရုံဖြစ်ပြီး မြန်မာနိုင်ငံတစ်ဝှမ်းသို့ အသုံးပြုသူများအား ရောင်းချနေဆဲဖြစ်ပါသည်။

-  Gray 1#
-  Gray 2#
-  Gray 3#
-  Gray 4#
-  Gray 5#
-  Gray 6#
-  Gray 7#
-  Gray 8#
-  Gray 9#
-  Cement Gray
-  Dull Gray
-  Silver Gray
-  Metal Gray
-  Luxury Silver
-  Glacier White
-  Calaeatta
-  Pearl Gold
-  Slate Gray
-  Terra Brown
-  Greyish Green
-  Yellow Gray
-  Soft Khaki
-  Yellowish Brown
-  Olive Brown
-  Brownness
-  Dark Brown
-  Reddish Brown
-  Rock Bslack



□□ □ □ □□□□ □□□□□□





01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Pointing Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

