

Kelin Polyurea 係 一種 耐用 且 易 於 安裝 之 塗料。 此 塗料 係 以 聚氨酯 為 主 材， 經 過 特殊 之 化學 反應 而 成。 其 具 有 優 異 之 耐 磨 損 性 能， 且 能 與 基 面 緊 密 結 合， 形 成 一 層 堅 硬 且 柔 韌 之 保 護 膜。 此 塗料 可 應 用 於 各 種 基 面， 如 金 屬、 木 材、 混 凝 土 等。 其 具 有 優 異 之 耐 腐 蝕 性 能， 且 能 有 效 地 防 止 基 面 受 到 酸 鹼 等 腐 蝕 性 物 質 之 損 壞。 此 塗料 之 施 工 簡 便， 且 能 在 短 時 間 內 完 成 塗 裝。 其 具 有 優 異 之 耐 污 染 性 能， 且 能 有 效 地 防 止 基 面 受 到 油 污 等 污 染 物 質 之 損 壞。 此 塗料 之 價 格 實 惠， 且 能 為 您 節 省 大 量 之 財 力。 此 塗料 係 一 種 實 用 且 耐 用 之 塗料， 誠 為 您 裝 修 之 最 佳 選 擇。



此 塗料 係 一 種 實 用 且 耐 用 之 塗料， 誠 為 您 裝 修 之 最 佳 選 擇。



□□ □□ □□ □□ □□ □□ □□

ENVIRONMENTAL (construction solid about 80-100%)

CONVENIENT CONSTRUCTION
(traditional construction method)

WATER PROOF (0.6mm Polyurea=2mm Polyurethane)

**3rd GENERATION
POLYUREA BASIC**

WEATHER RESISTANCE (qv2000h)

ENERGY CONSERVATION
(-5°Csolidify , primary film formation is 375um)

WEAR RESISTANCE (750g/500 times abrasion loss 30mg)
CORROSION RESISTANCE (salt fog resistance for 2000h)

□□ □ □ □□□□ □□□□□□






01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile




04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart




07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 2-4 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□ □ □ □ □ □



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Perching Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□ □ □ □



□□ □□



□□ □□ □□



□□□ □□□



□□ □□ □□




□□ □□ □□



□□ □□ □□



□□ □□ □□



□□ □□ □□



□□ □□ □□

□□

