

Kelin Polyurea 係 一種 耐用 且 易 於 安裝 之 塗料。 此 塗料 可 用於 牆面、 地板、 天花、 樓梯 等 各種 建築 表面。 其 優點 包括 抗 磨、 耐 刮、 易 於 清潔、 且 能 有效 防止 水 滲透 及 污 染。 此外， 該 塗料 還 具 有 優 異 之 粘 附 力， 能 與 各種 基 礎 材 質 緊 密 結 合。 總 之， Kelin Polyurea 係 一 種 實 用 且 經 濟 之 建築 塗料 選擇。

該 塗料 係 由 高 質 量 之 原料 製 成， 且 經 過 嚴 格 之 質 量 控 制。 其 研 究 與 開 發 (R & D) 部 門 不 斷 進 行 技 術 創 新， 以 應 付 不 同 之 應 用 需 求。 該 塗料 係 由 一 支 專 業 之 技 術 人 員 團 隊 研 發 出 來， 且 已 獲 得 多 項 國 際 性 質 量 認 證。



該 塗料 係 由 一 支 專 業 之 技 術 人 員 團 隊 研 發 出 來。










01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



02 Cutter Knife




03 Pointing trowel



04 Brush



05 Forming Stick



06 Pointing Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

□□ □□



□□ □□



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

□□

