

Kelin Waterborne Tile Grout 係 一種 環保 無 毒 無 異 味 無 揮 發 性 有 機 物 之 水 基 塗 料 。 其 具 有 優 越 之 粘 合 力 及 耐 磨 損 性 ， 且 具 有 優 異 之 防 水 防 污 功 能 。 此 種 塗 料 可 用 於 各 種 瓷 磚 之 鋪 設 ， 如 衛 浴 間 之 牆 面 及 地 面 ， 廚 房 之 牆 面 及 地 面 ， 及 各 種 瓷 磚 之 鋪 設 等 。 其 具 有 優 越 之 粘 合 力 及 耐 磨 損 性 ， 且 具 有 優 異 之 防 水 防 污 功 能 。 此 種 塗 料 可 用 於 各 種 瓷 磚 之 鋪 設 ， 如 衛 浴 間 之 牆 面 及 地 面 ， 廚 房 之 牆 面 及 地 面 ， 及 各 種 瓷 磚 之 鋪 設 等 。



此種塗料可應用於各種瓷磚之鋪設。



- Pure White
- Ivory
- Lemon Gold
- Pearl Gold
- Light Gold
- Lime Gold
- Amber Gold
- Nobility Gold
- Luxury Gold
- Shiny Gold
- Dazzle Gold
- Moonlight Silver
- Shiny Silver
- Dazzle Silver
- Light Gray
- Noble Gray
- Silver Gray
- Champaign Gold
- Bronze
- Rose Gold
- Coffee Brown
- Black Pearl

□□ □ □ □□□ □□□□□





Clean the tiles and keep it dry



Polish with tile wax except the glazed tile



Open & Watch, both sides can extruded meanwhile



Screw on the nozzle, put on the grout gun




Inclined cut the top of the nozzle in 45°



Squeeze out 60-80cm long grout in the forefront



Evenly squeeze out the tile agent along the gap



Press the grout with professional glue-press tools



Don't touch in 4-5 hours and remove excess grout then.




Keep the tiles dry in 24 hours

□□ □□ □□ □□



Two Component Caulking Gun



Cutter Knife

Pointing trowel

Brush

Forming Stick

Perching Knife

Masking Tape

Stainless Steel Ball

Cleaning Awl

□□ □□



□□ □□



□□ □□ □□



□□□ □□□



□□ □□ □□



□□ □□□



□□ □□ □□



□□ □□ □□



□□ □□ □□



□□ □□ □□

□□

